



Auburn Manufacturing Inc.
P.O. Box 220
Mechanic Falls, Maine 04256
U.S.A. 1-800-AMI-6689 • 207-345-8271
FAX: 207-345-3380

AMI-GLAS

ALUMINIZED AMI-GLAS CLOTH
STYLE #AGL2025-9383
06/18

STYLE NO: AGL2025-9383

NOMINAL WIDTH: 48" OR 60"

NOMINAL BASE FABRIC WEIGHT: 18.0 OZ/YD²

NOMINAL FINISHED WEIGHT: 20.5 OZ/YD²

NOMINAL THICKNESS: 0.031"

ALUMINUM FOIL: 0.001" THICK

BASE CLOTH TEMPERATURE RESISTANCE: 1000°F

ALUMINUM FOIL TEMPERATURE RESISTANCE: 1200°F

ADHESIVE TEMPERATURE RESISTANCE: 300°F

BASE FABRIC CONTENT: 100% FIBERGLASS YARNS

BASE FABRIC WEAVE: PLAIN

COUNT: WARP: 19
FILL: 14

MILITARY SPECIFICATIONS: MIL-C-20079H TYPE I CLASS 10 CAN BE MET IF REQUIRED.
REQUIREMENT MUST BE STATED ON PURCHASE ORDER

RAVEL RESISTANCE COATING AVAILABLE. COATING FINISHES DECOMPOSE AT TEMPERATURES BELOW
THE BASE FABRICS TEMPERATURE RESISTANCE

NOTE: RAVEL RESISTANCE COATED MATERIAL DOES NOT MEET MIL C 20079H TYPE 1 CLASS 10

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD
ALSO FAMILIARIZE THEMSELVES WITH THE SDS BEFORE HANDLING.

NOTE: WIDTH OF FINISHED PRODUCTS MAY BE NARROWER DUE TO THE LAMINATION PROCESS

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 07/08

Date Revised: 6/13/18

Date Reviewed: 6/13/18

Revision No.: 4

DOCUMENT IS UNCONTROLLED IF PRINTED